



XF-PTL05557-M72-11.48-VI

Specification

Optical structure	Bi-Telecentric
Magnification	1.079
Object field of view	Φ53.2mm
Image field of view	Φ57.4mm
Working Distance	138mm±3%
Telecentricity	<0.04°(0.08°)
Depth of field	1mm@F11
F#	F6-F76.5
Resolution	6.7μm@F11
MTF	>0.3@95lp/mm@F11
Distortion	<0.017%(0.10%)
Detector type:	

35film 36×24	33.4×22.2mm
2' 23×23	21.3×21.3mm
4/3' 18×13.5	16.7×12.5mm
1.1' 14.2×10.4	13.2×9.6mm
4K Linear scan 4096×7μm	26.6mm
8K Linear scan 8192×5μm	38.0mm
8K Linear scan 8192×7μm	53.1mm

Optional camera mount:
 1、M58×0.75
 2、M72×0.75

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL05557-M72-11.48-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.