



XF-PTL15244-M58-11.48

Specification

Optical structure	Bi-Telecentric
Magnification	0.293
Object field of view	Φ148.8mm
Image field of view	Φ43.6mm
Working Distance	320mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	11.3mm
F#	F9
Resolution	20.25μm
MTF	>0.3@115lp/mm
Distortion	<0.045%(0.100%)
Detector type:	
35film 36×24	122.9×81.9mm
2' 23×23	78.5×78.5mm
4/3' 18×13.5	61.4×46.1mm
1.1' 14.2×10.4	48.5×35.5mm
2K Linear scan 2048×10μm	69.9mm
4K Linear scan 4096×7μm	97.9mm
8K Linear scan 8192×5μm	139.8mm

Optional camera mount

- 1、 F
- 2、 M58×0.75
- 3、 M42×1

XF-PTLAAABB-C/F/P/M- (L90E)

The fourth generation lens of Canrill

Object FOV

Image FOV

The camera mount (M & P mount need specify BFL)

90° Steering option

Undefined tolerance (mm)	degree	File Name			
X. X	±0.2	±30min	XF-PTL15244-M58-11.48-外形尺寸-EN		
X. XX	±0.02	Drawing Name			
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.